



# Halogen Low Voltage

## 14515 FO 75W GX5.3 12V 1CT/10X5F

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.

### Product data

General Information	
Cap-Base	GX5.3 [GX5.3]
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]
Life to 50% Failures (Nom)	1,600 hour(s)
Light Technical	
Correlated Color Temperature (Nom)	2900 K
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	75 W
Voltage (Nom)	12 V
Voltage (Nom)	12 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Material	Quartz-UV Open
Reflector Finish	-
Bulb Shape	R50 [R 50mm]
Product Data	
Order product name	14515 FO 75W GX5.3 12V 1CT/10X5F
Full product name	14515 FO 75W GX5.3 12V 1CT/10X5F
Full product code	871150041099360
Order code	924034417104
Material Nr. (12NC)	924034417104
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500410993
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500423436

# Halogen Low Voltage

## Dimensional drawing



Product	D (max)	C (max)
14515 FO 75W GX5.3 12V 1CT/10X5F	50 mm	42 mm

