



Product Description

MASTER SDW-T

Range of high-efficiency, discharge lamps with warm colour to be used in open luminaires

Benefits

- Exceptional brightness and colour rendering especially of warm colours, e.g. red and gold
- High lamp efficacy results in low operating costs and low heat generation
- Long lamp life compared with incandescent and halogen lamps

Features

- Warm white colour impression, very good colour rendering, especially superb red rendition
- Lamp design is well-suited to be used in luminaires for power-spots (high intensity) and high-bay general lighting

Application

- Shop lighting (create cosy atmosphere e.g. in furniture shops), excellent display of fresh goods (at butchers, bakeries, flower-shops) and decorative outdoor lighting (gas-lantern imitation)

Warnings and Safety

- Use only with dedicated Philips control gear
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


MASTER SDW-T

Versions



LPPR SDW-T 100W PG12-1

Dimensional drawing



Product	D (max)	O	L	C (max)
MASTER SDW-T 100W/825 PG12-1 1SL/12	32 mm	18.3 mm	91 mm	149 mm
MASTER SDW-T 50W/825 PG12-1 1SL/12	32 mm	15.4 mm	91 mm	149 mm

General Information

Cap-Base	PG12-1
Operating Position	UNIVERSAL

Light Technical

Chromaticity Coordinate X (Nom)	0.478
Chromaticity Coordinate Y (Nom)	0.415
Color Designation	Golden White
Correlated Color Temperature (Nom)	2500 K

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	T31

Light Technical

Order Code	Full Product Name	Color rendering index (CRI)	Luminous Efficacy (rated) (Nom)	Luminous Flux
928153909227	MASTER SDW-T 50W/825 PG12-1 1SL/12	82	45.45 lm/W	2,500 lm
928154109227	MASTER SDW-T 100W/825 PG12-1 1SL/12	83	52.58 lm/W	5,100 lm

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
928153909227	MASTER SDW-T 50W/825 PG12-1 1SL/12	90 V	55.5 W

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
928154109227	MASTER SDW-T 100W/825 PG12-1 1SL/12	97 V	97.0 W

Mechanical and Housing

MASTER SDW-T

Order Code	Full Product Name	Bulb Material
928153909227	MASTER SDW-T 50W/825 PG12-1 ISL/12	Soft Glass

Order Code	Full Product Name	Bulb Material
928154109227	MASTER SDW-T 100W/825 PG12-1 ISL/12	Hard Glass

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Mercury (Hg) Content (Max)	Mercury (Hg) Content (Nom)
928153909227	MASTER SDW-T 50W/825 PG12-1 ISL/12	56 kWh	7.6 mg	7.6 mg
928154109227	MASTER SDW-T 100W/825 PG12-1 ISL/12	97 kWh	11.4 mg	11.4 mg

