



MASTER TL5 Circular

MASTER TL5 Circular 40W/865 1CT/10

16 mm tube diameter circular fluorescent lamps with a choice of various diameters

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	2GX13 [2GX13]

Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	3,100 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color rendering index (CRI)	82

Operating and Electrical	
Power Consumption	39.9 W
Lamp Current (Nom)	0.320 A

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	C-T5 [C-T5 16 mm]

Approval and Application	
Mercury (Hg) Content (Nom)	2.5 mg

Product Data	
Order product name	MASTER TL5 Circular 40W/865 1CT/10
Full product name	MASTER TL5 Circular 40W/865 1CT/10
Full product code	871150027650600
Order code	927965586513
Material Nr. (12NC)	927965586513
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500276506
Numerator - Packs per outer box	10
EAN/UPC - Case	8711500276469


MASTER TL5 Circular

Dimensional drawing




Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 40W/865 1CT/10	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm

Photometric data




Spectral Power Distribution Colour - MASTER TL5 Circular 40W/865 1CT/10

Lifetime




Life Expectancy Diagram - MASTER TL5 Circular 40W/865 1CT/10



Life Expectancy Diagram - MASTER TL5 Circular 40W/865 1CT/10

MASTER TL5 Circular

Lifetime



Lumen Maintenance Diagram - MASTER TL5 Circular 40W/865 1CT/10

