



T5 Preheat

F4T5/CW PH 25PK

Philips T5 Fluorescent Lamps are incredibly powerful, environmentally responsible, long life lamps with an ultra-slim profile. This translates into reduced maintenance and disposal costs and also allows the use of smaller fixtures—which reduces ceiling clutter.

Product data

General Information	
Cap-Base	G5 [G5]
Life to 50% Failures (Nom)	10,000 hour(s)

Light Technical	
Color Code	33-640
Luminous Flux	140 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	35 lm/W
Color rendering index (CRI)	60

Operating and Electrical	
Power Consumption	4 W
Lamp Current (Nom)	0.170 A
Voltage (Nom)	29 V
Voltage (Nom)	29 V

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Shape	T5 [16 mm (T5)]


Approval and Application	
Mercury (Hg) Content (Nom)	4.4 mg
Energy Consumption kWh/1000 h	5 kWh

Product Data	
Order product name	F4T5/CW PH 25PK
Order code	928000003321
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928000003321
Full product name	F4T5/CW PH 25PK
EAN/UPC - Case	50046677332360
EAN/UPC - Product/Case	046677332365


T5 Preheat

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
F4T5/CW PH 25PK	16 mm	135.9 mm	143.0 mm	140.6 mm	150.1 mm



Photometric data



Spectral Power Distribution Colour - F4T5/CW PH 25PK

