



A-Shape LED

9A19/PER/850/P/E26/DIM 8/1FB

Philips A-shape LED lamps are the LED alternative to standard incandescents. It provides beautiful light and dependable performance you expect from LED at an affordable price.


Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	850 [CCT of 5000K]
Beam Angle (Nom)	250 degree(s)
Luminous Flux	800 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	88.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	9 W
Lamp Current (Nom)	100 mA
Wattage Equivalent	60 W

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	85 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A19 [A 19mm]
Product Data	
Order product name	9A19/PER/850/P/E26/DIM 8/1FB
Full product name	9A19/PER/850/P/E26/DIM 8/1FB
Order code	929001836584
Material Nr. (12NC)	929001836584
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677471484
Numerator - Packs per outer box	8
EAN/UPC - Case	50046677479812



A-Shape LED

Dimensional drawing




Product	D	C
9A19/PER/850/P/E26/DIM 8/1FB	62 mm	111.3 mm

Photometric data



Spectral Power Distribution Colour - 9A19/PER/850/P/E26/DIM 8/1FB


Light Distribution Diagram - 9A19/PER/850/P/E26/DIM 8/1FB




General uniform lighting - 9A19/PER/850/P/E26/DIM 8/1FB

A-Shape LED

Lifetime



Lumen Maintenance Diagram - 9A19/PER/850/P/E26/DIM 8/1FB



Life Expectancy Diagram - 9A19/PER/850/P/E26/DIM 8/1FB

