



SlimSurface LED Downlight

SlimSurface LED downlight, 5-inch round, surface mount, 90 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish

SlimSurface LED downlight, 5-inch round, surface mount, 90 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish

SlimSurface LED is a low profile downlight intended for ceiling or wall mount applications. This 0.625" thick luminaire offers the appearance of a recessed downlight but is actually surface mounted.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	2700K
CRI	90
Downlight Type	Open Downlight
Photometric Distribution Type	Direct
Mounting	Surface Wall

Operating and Electrical	
Luminaire Input Watts	10
Voltages	120 V

Mechanical and Housing	
Aperture Size Code	5 in

Shape	Round
-------	-------

Initial Performance (IEC Compliant)	
Luminaire Lumens	650

Product Data	
Order product name	SlimSurface LED downlight, 5-inch round, surface mount, 90 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish
Commercial Code	S5R927K7
Order code	S5R927K7
Catalog Number Description	SlimSurface LED downlight, 5-inch round, surface mount, 90 CRI, 2700K CCT, 650 lm, 120V, Standard (TRIAC) dimming, wet location, Matte White Finish

SlimSurface LED Downlight

Service / Spec Smart	Service Smart (2 Days) USA
Material Nr. (12NC)	LIGU60011114

